



US 20040227736A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0227736 A1**  
(43) **Pub. Date: Nov. 18, 2004**(54) **CAPACITOR BASED FORCE SENSOR**(52) **U.S. Cl. .... 345/173**(76) **Inventors: Robert F. Kamrath**, Mahtomedi, MN (US); **Michael E. Hamerly**, Vadnais Heights, MN (US); **Billy L. Weaver**, Eagan, MN (US)(57) **ABSTRACT**

Correspondence Address:

**3M INNOVATIVE PROPERTIES COMPANY**  
**PO BOX 33427**  
**ST. PAUL, MN 55133-3427 (US)**

The invention provides a novel capacitive device configured to detect differences in an applied force over a continuous range of applied force that includes zero force. The device includes first and second electrodes that are spaced apart a predetermined distance from each other in a rest position. A measurable capacitance exists between the first and second electrodes. Structured elements having a predetermined maximum dimension are positioned in the device to control the predetermined distance between the first and second electrodes. An applied force to the device causes a change in the distance between the first and second electrodes and a related change in the capacitance that can be measured to determine information related to the applied force.

(21) **Appl. No.: 10/439,447**(22) **Filed: May 16, 2003****Publication Classification**(51) **Int. Cl.<sup>7</sup> ..... G09G 5/00**